

Declaration of Performance

DOP REF: CAN-01-2026
PRODUCT: Canterra® range
ISSUE DATE: 1 April 2026
MANUFACTURING STANDARD: hEN 1339 : 2003
COMPLIANCE CATEGORY: Attestation Level 4
PLANT OF MANUFACTURE: AG 127 Crievehill Road, Fivemiletown, Co. Tyrone, BT75 0SY
APPLICATION: External / Commercial / Retail / Residential / Pedestrian Areas / Vehicular Overrun

Declared Performance

| Essential Requirements | Performance Value |
|-------------------------------|---|
| Surface Layer | Durable and hard wearing with a minimum surface layer of 8mm |
| Granite Content | Not less than 50% natural granite and quartz aggregate in surface layer |
| Efflorescence | State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction |
| Bending Strength (Flagstones) | >3.5Mpa. This pressure applies to all sizes and depths. For specific force performance on a given size or depth please contact our Technical Specification Department |
| Slip / Skid Resistance | (PTV) >60 low potential for slip. Specific slip / skid resistance test results are available on request from our Technical Specification Department |
| Abrasion Resistance | Class 3 |
| Installed to | BS 7533-4:2006 |
| NBS Plus | Q25 315 |

Compliance is achieved by Factory Processed Control (FPC) system of testing and inspections to the relevant Standard.

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and when installed in accordance with BS 7533.

Signed:

Stephen Acheson, Chief Executive Officer

Dated: January 2026

