

DECLARATION OF PERFORMANCE

DOP REF:	COBB01-2023
PRODUCT:	Country Cobble® range
ISSUE DATE:	26 January 2023
MANUFACTURING STANDARD:	hEN 1338 : 2003
COMPLIANCE CATEGORY:	Attestation Level 4
PLANT OF MANUFACTURE:	AG 127 Crievehill Road, Fivemiletown, Co. Tyrone, BT75 0SY
APPLICATION:	External / Commercial / Retail / Residential / Pedestrian Areas / Vehicular Overrun

Declared Performance

Essential Requirements	Performance Value
Through Mix	Country Cobble® features an all-through mix
Efflorescence	State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Tensile Splitting Strength (Paving Blocks)	>3.6Mpa. This pressure applies to all paving blocks sizes and depths (Paving Blocks) For specific force performance on a given size or depth please contact our Technical Specification Department
Slip / Skid Resistance	Unpolished (USRV) >60 low potential for slip. Polished (USRV) >45 low potential for slip. Pendulum Test Value (PTV) test results are available on request from our Technical Specification Department
Frost Resistance	Class 3 : Resistance to freeze/thaw with de-icing salts = Mass loss after freeze/thaw test 1.0kg/m ² as a mean value with no individual value >1.5kg/m ²
Abrasion Resistance	Class 3 : </- less than or equal to 23mm
Light Reflectance Value (LRV)	Test results are available on request from our Technical Specification Department
Solar Reflectance Index (SRI)	Test results are available on request from our Technical Specification Department
Water Absorption (24hr)	6% max
Installed to	BS 7533-4:2006
NBS Plus	Q24 110

Compliance is achieved by Factory Processed Control (FPC) system of testing and inspections to the relevant Standard.

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and when installed in accordance with BS 7533.

Signed:

Stephen Acheson, Chief Executive Officer

Dated: January 2023

