

DECLARATION OF PERFORMANCE

DOP REF: **KAM01-2022**
PRODUCT: **Kamden Double Sided Walling**
ISSUE DATE: 1 February 2022
MANUFACTURING STANDARD: hEN 771-3:2011+A1:2015 - Specification for masonry units
COMPLIANCE CATEGORY: **Attestation Level 4**
PLANT OF MANUFACTURE: AG 127 Crievehill Road, Fivemiletown, Co. Tyrone, BT75 0SY
APPLICATION: External Double Sided Wall Structures

Declared Performance

Essential Requirements	Performance Value				
	Kamden Block	Half Block	Corner Block	Stop End Block	ShortCut™ Cap
Dimensions	L 220 x D 260 x H 150mm Short side length: 176mm	L 110 x D 260 x H 150mm Short side length: 88mm	L 150 x D 255 x H 150mm	L 195 x D 255 x H 150mm Short side length: 175mm	L 200* x D 330 x H 75mm Short side length: 175mm
Compressive Strength	24 N/mm ²	24 N/mm ²	24 N/mm ²	24 N/mm ²	N / A
Durability	Adequate for purpose				
Reaction to fire	A1				
Max. Gravity Wall Build Height	Max. up to 0.9m for both gravity and freestanding walls. Engineered N/A.	N / A	N / A	N / A	N / A
Wall height above 0.9m	N / A	N / A	N / A	N / A	N / A
Set Back / Face Angle	N / A	N / A	N / A	N / A	N / A
Minimum inside radius (to back of block on bottom course)	2.04m	N / A	N / A	N / A	N / A
Minimum outside radius (to front of block on bottom course)	2.56m	N / A	N / A	N / A	N / A
Tolerances on all dimensions (mm)	±2mm	±2mm	±2mm	±2mm	±2mm
Face finish	Stone cut	Straight Cut	Straight Cut	Straight Cut	Straight Split
Face geometry	Stretcher	Stretcher	Stretcher	Stretcher	Stretcher

Compliance is achieved by Factory Processed Control (FPC) system of testing and inspections to the relevant Standard.

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations.

Signed:

Stephen Acheson, Chief Executive Officer

Dated: January 2022

