

DECLARATION OF PERFORMANCE

DOP REF: MS01-2022
PRODUCT: Manor Stone® range
ISSUE DATE: 5 January 2022
MANUFACTURING STANDARD: hEN 1339 : 2003
COMPLIANCE CATEGORY: Attestation Level 4
PLANT OF MANUFACTURE: AG 60 Creagh Road, Toome, Co. Antrim, BT41 3SE
APPLICATION: External / Commercial / Retail / Residential / Pedestrian Areas / Vehicular Overrun

Declared Performance

Essential Requirements	Performance Value
Surface Layer	Durable and hard wearing with a minimum surface layer of 8mm. Minimum cement content 380kg/m ³
Granite Content	Not less than 50% natural granite and quartz aggregate in surface layer
Efflorescence	State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Bending Strength (Flagstones)	>3.5Mpa. This pressure applies to all sizes and depths. For specific force performance on a given size or depth please contact our Technical Specification Department
Slip / Skid Resistance	(USRV) >75 extremely low potential for slip. Specific slip / skid resistance test results are available on request from our Technical Specification Department
Installed to	BS 7533-4:2006
NBS Plus	Q25 315

Compliance is achieved by Factory Processed Control (FPC) system of testing and inspections to the relevant Standard.

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and when installed in accordance with BS 7533.

Signed:

Stephen Acheson, Chief Executive Officer

Dated: January 2022

