

# DECLARATION OF PERFORMANCE


**DOP REF:** TACT01-2023  
**PRODUCT:** Tactile range  
**ISSUE DATE:** 23 February 2023  
**MANUFACTURING STANDARD:** hEN 1339:2003 and DD CEN/TS 15209: 2008  
**COMPLIANCE CATEGORY:** Attestation Level 4  
**PLANT OF MANUFACTURE:** AG 127 Crievehill Road, Fivemiletown, Co. Tyrone, BT75 0SY  
**APPLICATION:** External / Commercial / Retail / Residential / Pedestrian Areas / Vehicular Overrun

## Declared Performance

Essential Requirements	Performance Value
Surface Layer	Durable and hard wearing with a minimum surface layer of 8mm. Minimum cement content 380kg/m <sup>3</sup>
Granite Content	Not less than 50% natural granite and quartz aggregate in surface layer
Efflorescence	State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Bending Strength (Flagstones)	>5.0Mpa. This pressure applies to all sizes and depths. For specific force performance on a given size or depth please contact our Technical Specification Department
Slip / Skid Resistance	>60 low potential for slip. Specific slip / skid resistance test results are available on request from our Technical Specification Department.
Installed to	BS 7533-4:2006
NBS Plus	Q25 315

Compliance is achieved by Factory Processed Control (FPC) system of testing and inspections to the relevant Standard.

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and when installed in accordance with BS 7533.

Signed: 

Stephen Acheson, Chief Executive Officer

Dated: February 2023

