

DECLARATION OF PERFORMANCE


DOP REF: XFLOHP01-2022
PRODUCT: Xflo HomePave permeable paving range
ISSUE DATE: 15 August 2022
MANUFACTURING STANDARD: hEN 1338 : 2003
COMPLIANCE CATEGORY: Attestation Level 4
PLANT OF MANUFACTURE: AG 60 Creagh Road, Toome, Co. Antrim, BT41 3SE
APPLICATION: External / Commercial / Retail / Residential / Pedestrian Areas / Vehicular Overrun

Declared Performance

Essential Requirements	Performance Value
Surface Layer	Durable and hard wearing with a minimum surface layer of 8mm. Minimum cement content 380kg/m ³
Efflorescence	State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Tensile Splitting Strength (Paving Blocks)	>3.6Mpa. This applies to all sizes and depths. For specific force performance on a given size or depth please contact our Technical Specification Department
Slip / Skid Resistance	Low potential for slip
Water Absorption (24hr)	< 6%
Installed to	BS 7533-4:2006 / BS 7533-3:2005 + A1:2009 / BS 7533-13:2009
NBS Plus	Q24 110

Compliance is achieved by Factory Processed Control (FPC) system of testing and inspections to the relevant Standard.

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and when installed in accordance with BS 7533.

Signed: 

Stephen Acheson, Chief Executive Officer

Dated: August 2022

