

# DECLARATION OF PERFORMANCE

**DOP REF:** TRISTONE01-2023  
**PRODUCTS:** Tri Stone range  
**ISSUE DATE:** 1 March 2023  
**MANUFACTURING STANDARD:** hEN 1338 : 2003  
**COMPLIANCE CATEGORY:** Attestation Level 4  
**PLANT OF MANUFACTURE:** AG 60 Creagh Road, Toome, Co. Antrim, BT41 3SE  
**APPLICATION:** External / Commercial / Retail / Residential / Pedestrian Areas / Vehicular Overrun

## Declared Performance

Essential Requirements	Performance Value
Surface Layer	Durable and hard wearing with a minimum surface layer of 8mm. Minimum cement content 380kg/m <sup>3</sup>
Efflorescence	State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Tensile Splitting Strength (Paving Blocks)	>3.6Mpa. This applies to all sizes and depths. For specific force performance on a given size or depth please contact our Technical Specification Department. HomePave 50mm is suitable for driveways with cars, caravans, vans, motorhomes, etc.
Slip / Skid Resistance	Low potential for slip
Water Absorption (24hr)	< 6%
Installed to	BS 7533-4:2006
NBS Plus	Q24 110

Compliance is achieved by Factory Processed Control (FPC) system of testing and inspections to the relevant Standard.

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and when installed in accordance with BS 7533.

Signed:

**Stephen Acheson**, Chief Executive Officer

Dated: March 2023

