

Declaration of Performance

DOP REF: HEATH-2026-01
PRODUCT: Heathfield Facing Brick
ISSUE DATE: 13 May 2026
MANUFACTURING STANDARD: hEN 771-3: 2011+A1 : 2015
PLANT OF MANUFACTURE: AG 60 Creagh Road, Toome, Co. Antrim, BT41 3SE
APPLICATION: Facing brick for use on commercial and domestic buildings

Declared Performance

Essential Requirements	Performance Value
Dimensions	L 215 x D 102.5 x H 65mm
Compressive Strength*	Min average 22 N/mm ²
Water Absorption (24hr)	6% max
Durability Designation	F2 Severe Exposure
Mean Coefficient Of Water Absorption	4.4 g / (m ² .s)
Moisture Movement Coefficient**	0.46 mm / m
Active Soluble Salts [So3]	0.03%
Size Tolerance	hEN 771-3: 2011 (T1) Category D2
Gross Density	2200 Kg / m ³
Dangerous Substances	None

Essential Requirements	Performance Value
Thermal Conductivity	1.56 W / m.K
Initial Rate Of Absorption	0.42 Kg / m ² .m-1
Bond Strength	0.15 N / mm ²
Reaction To Fire	A1 Class
Type Of Mortar	Recommended ratio 6 : 1 or 5 : 1 Sand : OPC
Water Vapour Permeability [U]	5 / 15u tabulated from EN 1745
Pack Quantity	504
Pack Size [Apx. Mm]	L 1300 x D 800 x H 800mm
Typical Pack Weight	1400 Kg
Packaging (Full Shrink Bag)	Palletted

* Compressive strength in accordance with PD 6697 : 2010 and Eurocode 6.

** Determination of moisture movement and drying shrinkage carried out in accordance with hEN 772-14:2001 (E)

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and when built in accordance with NHBC Guidelines.

Signed: 

Stephen Acheson, Chief Executive Officer

Dated: 13 May 2026

