Declaration of Performance

DOP REF:	**CLAS-2026-01**
PRODUCT:	**Classic Facing Brick**
ISSUE DATE:	13 May 2026
MANUFACTURING STANDARD:	hEN 771-3: 2011+A1 : 2015
PLANT OF MANUFACTURE:	AG 60 Creagh Road, Toome, Co. Antrim, BT41 3SE
APPLICATION:	Facing brick for use on commercial and domestic buildings

Declared Performance

Essential Requirements	Performance Value
Dimensions	L 215 x D 102.5 x H 65mm
Compressive Strength*	Min average 22 N/mm²
Water Absorption (24hr)	6% max
Durability Designation	F2 Severe Exposure
Mean Coefficient Of Water Absorption	1.5 g / (m².s)
Moisture Movement Coefficient**	0.46 mm / m
Active Soluble Salts [So3]	0.03%
Size Tolerance	hEN 771-3: 2011 (T1) Category D3
Gross Density	2200-2300 Kg / m³
Dangerous Substances	None

Essential Requirements	Performance Value
Thermal Conductivity	1.56 W / m.K
Initial Rate Of Absorption	0.42 Kg / m².m-1
Bond Strength	0.15 N / mm²
Reaction To Fire	A1 Class
Type Of Mortar	Recommended ratio 6 : 1 or 5 : 1 Sand : OPC
Water Vapour Permeability [U]	5 / 15u tabulated from EN 1745
Pack Quantity	540
Pack Size [Apx. Mm]	L 1080 x D 930 x H 800mm
Typical Pack Weight	1500 Kg
Packaging (Full Shrink Bag)	Palleted

* Compressive strength in accordance with PD 6697 : 2010 and Eurocode 6.
** Determinination of moisture movement and drying shrinkage carried out in accordance with hEN 772-14:2001 (E)

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and when built in accordance with NHBC Guidelines.

Signed: _____

Stephen Acheson, Chief Executive Officer

Dated: 13 May 2026