



Acheson & Glover

NS Plus



Plaza Paving and Flags

By Acheson & Glover

Detailed description

Plaza is a range of small to large element paving manufactured from premium quality selected granite and other natural aggregates. The textured washed surface gives the appearance of natural granite stone but with the quality assurance of concrete block paving. Plaza provides a contemporary backdrop for either modern or traditional schemes and is suitable for all types of loading from pedestrian to heavy duty traffic. (Depending upon module size selected). Consult Acheson & Glover technical literature for further details.

Product guidance - As Standard

Standard:

Manufactured to BS EN 1338.

- Weathering resistance: Class 3.
- Potential for slip: Low.
- Abrasion resistance: Class 3.

Finish:

Textured stone washed.

Sustainability;

- Energy use: 100% renewable energy.
- Water used: 100% rain water harvesting.
- Recycled non primary material content: 52–60%.
- Recyclability: 100% of this product can be recycled.
- Manufacturing location: Produced in the UK with locally sourced materials.
- Waste wood and plastic: 100% recycled.
- Carbon footprint: 18– 20 kg CO2/m² (dependent upon thickness).Carbon footprint: 18– 20 kg CO2/m² (dependent

upon thickness). Carbon footprint: 18– 20 kg CO₂/m² (dependent upon thickness).

- BREEAM rating: A, in accordance with the Green Guide to specification (A+ rating can be achieved by using a recycled sub-base).

CE marking:

CE marked; Certificate 04/1-7-13, attestation Level 4 CPR (2011) Annex V.

Options

Permeable paving:

Xflo permeable paving blocks 170 x 170 and 255 x 170 x 80 mm thick, are also available in Plaza finish and colours.

Product specification

Manufacturer

- Name: Acheson & Glover
- Web: www.acheson-glover.com
- Email: solutions@acheson-glover.com
- Tel: +44 (0)28 8952 1275
- Fax: +44 (0)28 8952 1866
- Address: 127 Crievehill Road, Fivemiletown, Co Tyrone BT75 0SY

Product reference	Plaza Paving and Flags
Size	150 x 150 mm - 60 mm thickness. 200 x 150 mm - 60 mm thickness. 300 x 150 mm - 60 mm thickness. 200 x 100 mm - 80 mm thickness. 200 x 200 mm - 80 mm thickness. 400 x 200 mm - 80 mm thickness. 400 x 400 x 50 mm - 50 mm thickness. 400 x 400 mm x 80 mm - 80 mm thickness.
Colour	Graphite - Only available in 80 mm thick paving. Slate Sandstone Silver
Jointing sand	Buff - For Sandstone colour flags. Silver granite - For silver/ slate colour flags.
Other requirements	Reconstituted granite kerbs Tactile flags