

DECLARATION OF PERFORMANCE

DOP REF: **RECT01-2021**
PRODUCTS: **Rectangular range**
ISSUE DATE: 07 January 2021
MANUFACTURING STANDARD: BS EN 1338 : 2003
COMPLIANCE CATEGORY: **Attestation Level 4**
PLANT OF MANUFACTURE: AG 60 Creagh Road, Toome, Co. Antrim, BT41 3SE
APPLICATION: External / Commercial / Retail / Residential / Pedestrian Areas / Vehicular Overrun

Declared Performance

Essential Requirements	Performance Value
Surface Layer	Durable and hard wearing with a minimum surface layer of 4mm
Efflorescence	State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Tensile Splitting Strength (Paving Blocks)	>3.6Mpa. This pressure applies to all sizes and depths.
Installed to	BS 7533-4:2006
NBS Plus	Q24 110

Compliance is achieved by Factory Processed Control (FPC) system of testing and inspections to the relevant Standard.

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and when installed in accordance with BS 7533.

Signed: 

Stephen Acheson, Chief Executive Officer

Dated: January 2021

